

Product	Power Supply, Open-Frame Building-in Type
Applicant	Astec International Ltd. 16th Floor, Lu Plaza, 2 Wing Yip Street, Kwun Tong, Kowloon, Hong Kong
Manufacturer	Astec International Ltd. 16th Floor, Lu Plaza, 2 Wing Yip Street, Kwun Tong, Kowloon, Hong Kong
Factory	<input checked="" type="checkbox"/> See page 2
Ratings	AC input: 1.6A 100-250V 50/60/440Hz or DC input: 1.0A 120-300Vdc
Trade mark	ASTEC
Model / Type Ref.	LPT42
Principal characteristics	Cl. I, DC-outputs: 5A +5V, 2.5A +12V, 0.7A -12V. Maximum continuous output power is 40W (convection cooling). Maximum continuous output power is 55W (30CFM forced cooling). <input type="checkbox"/> See next page(s)
A sample of the product was tested and found to be in conformity with	OFF                      EN 60950-1:2006;A11;A1;A12;A2
Validity	This certificate documents conformity with the standards shown, and also applies as license for use of Nemkos name and certification mark. The certificate and license is valid as long as the applicable conditions are complied with, and provided that any changes to the product are notified to Nemko for acceptance prior to implementation. New standards or amendments to the standards may imply that the product design must be updated and/or that re-testing and re-certification is necessary.
Additional information	<input type="checkbox"/> See next page(s)  The abovementioned certified equipment complies with current regulatory requirements regarding electrical safety in Norway and other EU/EEA member states, as far as this can be checked. Compliance with requirements regarding building-in, protection against electric shock and Electromagnetic Compatibility (EMC) must be checked when the equipment is built-in a completed product or forms a part of a complete system.
Additional model(s)	<input checked="" type="checkbox"/> See next page(s)

Date of issue 15-07-2015



Nastaran Vadoodi  
Certification Department

Product Power Supply, Open-Frame Building-in Type  
Pos. No 1  
Model / Type Ref. LPT43  
Trade mark (if different from page 1)  
Rating AC input: 1.6A 100-250V 50/60/440Hz or DC input: 1.0A 120-300Vdc  
Principal characteristics Cl. I, DC-outputs: 8A +5V, 0.7A +12V, 0.7A -12V. Maximum continuous output power is 40W (convection cooling). Maximum continuous output power is 55W (30CFM forced cooling).

Product Power Supply, Open-Frame Building-in Type  
Pos. No 2  
Model / Type Ref. LPT44  
Trade mark (if different from page 1)  
Rating AC input: 1.6A 100-250V 50/60/440Hz or DC input: 1.0A 120-300Vdc  
Principal characteristics Cl. I, DC-Outputs: 5A +5V, 2.5A +12V, 0.7A -5V. Maximum continuous output power is 40W (convection cooling). Maximum continuous output power is 55W (30CFM forced cooling).

Product Power Supply, Open-Frame Building-in Type  
Pos. No 3  
Model / Type Ref. LPT45  
Trade mark (if different from page 1)  
Rating AC input: 1.6A 100-250V 50/60/440Hz or DC input: 1.0A 120-300Vdc  
Principal characteristics Cl. I, DC-Outputs: 5A +5V, 2.5A +15V, 0.7A -15V. Maximum continuous output power is 40W (convection cooling). Maximum continuous output power is 55W (30CFM forced cooling).

Factories:

Astec Power Philippines Inc.  
Main Avenue Corner Road "J" Cavite Export Processing  
Zone Rosario, Cavite 4106,  
Philippines

Astec Power Philippines Inc.  
104 Laguna Blvd., Laguna Technopark, Sta. Rosa  
Laguna 4026,  
Philippines

Date of issue 15-07-2015



Nastaran Vadoodi  
Certification Department

**Nemko AS**

Gaustadalléen 30, P.O. Box 73 Blindern, 0314 Oslo, Norway  
TEL +47 22 96 03 30 FAX +47 22 96 05 50 EMAIL info@nemko.com  
ENTERPRISE NUMBER NO974404532